

**SERIES**  
**B**

# B15

## POS Terminal Machine

Enhanced POS Solutions

*Fan-Less designed for Hospitality Service*



10 point touch

### #Key Features


- #True Flat P-CAP Touch
- #Water Splash Resistant
- #10 Point Touch Screen
- #Fanless Technology



### Designed for Hospitality Service



Intel Celeron J1900 | Core i3



2GB | 4GB | 8GB SODIMM DDR3



M-SATA 64GB | 128GB



15" Projective Capacitive



Model	PM-B15-J1926C	PM-B15-I326C
CPU	Intel Celeron Bay Trail D J1900 Quad Core up to 2.4G (2M Cache Fanless)	Intel Core i3, i3-3217U Dual Core 1.8G 3MB Cache
Chipset	Bay Trail DJ1900	I3-3217U+HM76
Memory	2GB DDR3 (up to 8GB)	2GB DDR3 (up to 8GB)
HDD	64GB/128GB MSATA SSD	64GB/128GB MSATA SSD
Interface/ Port	4xUSB / 1xCOM/ 1xLPT/ 1xVGA/ 1xPS2/ 2xAudio / 2x10/100/1000 Base-T	
Touch Monitor	15" Projected Capacitive Touch (1024x786) TRUE - FLAT SCREEN Brightness 300 cd/m2 Contrast 600:1 Response time 8ms	
Dimension	360(W) X 300(L) X 51.99 (H) mm	
Operation Condition	Temperature: up to 40 degree Humidity: 10 to 80%	
Add On VFD-BT15 PM8 MSR-BT15 WIFI OS	20*2 lines VFD Customer Display 8" Monitor Display MSR Card 1.2.3 Track Reader Wifi Module Window XP/7/8/10   POS Ready 2009 / 7 / 10 IOT	

