



## Kitchen & Bar Solutions Printer

### Specifications

Model	PP-T6B
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5 ± 0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE/PDF417
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、 PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、 Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、 PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V = 2.5A
Cash drawer control	DC 24V = 1A
Interface	Serial+USB+Lan
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 10/Linux/OPOS
Command	Compatible with ESC/POS
Gross weight	1.81 kg
Dimension	193.3 × 145 × 144mm (D × W × H)

### Key features

- Support QR CODE Printing
- Support Chinese GB18030
- 100MB Ethernet interface connection
- Avoid order missing
- Support black mark orientation
- Support water splash proof
- Support 2048KB input buffer
- Support wall mountable and truck cable

